




Wire Rope Sling




Both End With Thimble



Both End With Mechanical Thimble



Both End With Thimble



Both End With Soft Eye

Detail Information About The Thimbles

Connect NO	Diameter mm	Total Base Area Of Wire Rope		Lb		Sleeve Compression Diameter mm
		min (mm)	max (mm)	min (mm)	max (mm)	
6	6.2	14.2	15.1	100	150	13
10	9.3	31.9	34.0	120	200	20
14	13.0	72.0	77.0	150	250	28
18	17.5	113.1	120.3	200	350	36
20	19.5	147.7	157.1	250	400	40
22	21.5	170.6	181.2	250	400	44
24	24.0	212.6	226.2	350	500	48
26	26.0	249.5	265.5	400	600	52
30	30.0	341.6	370.0	500	700	60
34	34.5	446.1	470.0	600	900	68
40	39	590.6	628.3	700	1000	80
44	43.0	682.5	726.1	700	1000	88
52	52.0	998.2	1061.9	800	1200	104
56	56.0	1157.6	1231.5	1000	1500	112
60	60.5	1351.1	1437.4	1000	1500	120

Specification

- Material :Wire Rope with Intensity is based on 1770N/mm²
- Remark: Sling Length, Diameter and Structure upon request